



Concentrated Primer

PRODUCT DESCRIPTION

Water-based, concentrated primer with high penetration and adhesion performance.

SPECIFICATIONS

Enables the paint to adhere better to the surface by creating a binding bridge between the paint and the surface. Decreases the absorbing power of the surface, prevents the paint from drying too fast and eliminates the color changes that may be seen on the top coat paints of surfaces with different absorbing capacities. Saves money by decreasing paint consumption.

APPLICATION SURFACES

Applied on plaster, lime whitewash, low quality absorbent plastic painted surfaces that lost their quality, and highly absorbing and/or high dust generating surfaces like aerated concrete.

APPLICATION

Ensure the application surface is dry, clean and self-supporting. Apply the primer on plaster or similar surfaces after they are sanded and dusted with a moist cloth / a moist car wash brush. Thin as required and apply to the surface using a brush or a roller without combing/polishing. Ensure the ambient temperature is between +5°C and +30°C during application. Protect the surface from frost during primer application and drying. Start the paint application minimum 4 hours after applying Fawori Concentrated Primer. It is definitely not recommended to use the primer for insulation purposes by thinning with less water or combing and to use the primer on paste with glue or solvent-based primer and paint.

WARNING

There should not be any glassy layer on the surfaces that Fawori Concentrated Primer is applied. Such glassy layers should be removed from the surface by sanding or mechanical methods, and the surface should be dulled. Otherwise, there may be peeling, cracking, blistering, roller tracks and coverage problems. It should never be applied with Airless (spraying) method and without thinning. Our products should be applied on substructure surfaces that are built in line with General Construction Specifications dated 30.06.2007 and with No. 26568.

THINNING

Thin 1 unit of primer with 7 units of water for silicone paints, and 1 unit of primer with 10 units of water for plastic paints.

DRYING TIME (at 20°C, 65% RH)

Touch dry: 1 hours

Paint application: 4 hours (drying time may increase at higher relative humidity and lower temperature)

CONSUMPTION

Depending on the type, absorbency and structure of the application surface an area of 40-65 m² can be primed in a single coat with 1 liter (if thinned in the ratio of 1:7). Perform a controlled sample run to estimate the precise consumption amount.

STORAGE

It can be stored in its unopened package for 3 years, in a cool and dry place, away from frost and direct sunlight. Close the lid air-tight immediately after application.

PACKAGE

9 L, 5 L, 2.5 L

WARNING STATEMENT

Caution

HAZARD STATEMENT

H317 May cause an allergic skin reaction.



PRECAUTIONARY STATEMENTS

P101 If medical advice is needed, have the product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P261 Avoid breathing its dust/fume/gas/mist/vapors/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P333+P313: If skin irritation or a rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local, regional, national and international regulations.

This technical sheet is prepared based on laboratory data at normal conditions. Consult technical personnel for details that are not provided above. Otherwise, the manufacturing company cannot be held responsible for failures that may arise due to lack of knowledge. Our company reserves the right to change the information provided.

This product is manufactured by Betek A.Ş., with certificate of conformity to the standards TS EN ISO 9001, TS EN ISO 14001, TS 18001, TS EN ISO 50001, TS ISO 10002, TS ISO/IEC 27001.

Rev4 March 2020