



Master Paint

PRODUCT DESCRIPTION

Silicone, acrylic copolymer emulsion-based, matte, exterior facade top-coat paint.

SPECIFICATIONS

- ✓ Contains silicone
- ✓ Matte
- ✓ Vivid color options
- ✓ High level of water repelling
- ✓ Breathable
- ✓ 5-year UV-resistance guarantee
- ✓ Resistant to friction and impacts

Holds on to the application surface well thanks to its superior adherence power. Resistant to atmospheric conditions, air pollution, and solar rays. Enables the moisture on the surface to be released thanks to its breathability. Easy to apply, spreads easily over the surface.

APPLICATION SURFACES

Can be applied to plaster, rough plaster, comb mosaic, polished mosaic, concrete, brute concrete, concrete board, MDF, OSB, and even to old painted ready-plaster type surfaces that can still support themselves even though they may have lost their color.

APPLICATION

Ensure the application surface is firm, dry, clean and self-supporting. Remove all types of stain, dust, block grease and loose layers. Observe the setting period (28 days) on concrete, brute concrete, new plastered surfaces, and clean the loose plaster particles with scraper or similar methods. Correct and repair the surface if required. Begin painting after applying the appropriate primer. Avoid application between 10 AM and 04 PM during hot weather conditions. Recommended to be applied to shady walls. Ensure the ambient and surface temperatures are between +5°C and +30°C, and protect the surface from all kinds of precipitation, dew and frost.

Our products should be applied on substructure surfaces that are built in line with 30.06.2007 dated General Construction Specifications No. 26568.

For airless spraying:

Pressure: 140 bar
Nozzle Angle: 50°C
Nozzle Size (inch): 0.019"-0.021"
Thinning: 5%

THINNING

Thin by max. 15% with clean water in applications with brush and roller, and by max. 5% with clean water in spraying. Ensure all products are thinned at the same rate in order to prevent color tone differences.

DRYING TIME (at 20°C, 65% RH)

Touch dry: 1-2 hours
Dry period between the primer and the coats : 6-8 hours
Final-dry : 24 hours

BETEK BOYA VE KİMYA SAN. A.Ş.



CONSUMPTION

Depending on the type, absorbency and structure of the surface to be applied, an area of 7-10 m² can be painted with 1 liter in a single layer. Perform a controlled sample run to estimate the precise consumption amount.

STORAGE

It can be stored in its unopened package for 3 years, in a cool and dry place, away from frost and direct sunlight. Close the lid air-tight immediately after application..

PACKAGE

9 L, 5 L, 2.5 L

WARNING STATEMENT

Caution

HAZARD STATEMENT

H317 May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

P101 If medical advice is needed, have the product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P261 Avoid breathing its dust/fume/gas/mist/vapors/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P333+P313: If skin irritation or a rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local, regional, national and international regulations.



Protect the surfaces from extreme dew and rain especially during the period from the cement-based surface correction / repair paste application to the final coat application. Otherwise, there will be efflorescence. In such a case, moisten the surface with a car wash brush and apply 1 unit of Disboxan 451 + 1 unit of water mixture.

For airless spraying:

Pressure: 140 bar
Nozzle Angle: 50°C
Nozzle Size (inch): 0.019"-0.021"
Thinning: 5%

THINNING

Thin by max. 15% with clean water in applications with brush and roller, and by max. 5% with clean water in spraying. Ensure all products are thinned at the same rate in order to prevent color tone differences.

DRYING TIME (at 20°C, 65% RH)

Touch dry: 1-2 hours
Dry period between the primer and the coats: 6-8 hours
Final-dry : 24 hours

CONSUMPTION

Depending on the type, absorbency and structure of the surface to be applied, an area of 7-10 m² can be painted with 1 liter in a single layer. Perform a controlled sample run to estimate the precise consumption amount.

STORAGE

It can be stored in its unopened package for 3 years, in a cool and dry place, away from frost and direct sunlight. Close the lid air-tight immediately after application..

PACKAGE

15 L, 7.5 L, 2.5 L

WARNING STATEMENT

Caution

HAZARD STATEMENT

H317 May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

P101 If medical advice is needed, have the product container or label at hand.
P102 Keep out of reach of children.
P103 Read label before use.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P333+P313: If skin irritation or a rash occurs: Get medical advice/attention.
P501 Dispose of contents/container in accordance with local, regional, national and international regulations.



Conforms to TS 7847.



Conforms to the G communiqué.

TSE

Pos. No.

27,560/7

Rate No

04.522/S

This technical sheet is prepared based on laboratory data under normal conditions, consult the technical personnel for details that are not provided above. Otherwise, the manufacturing company cannot be held responsible for failures that may arise due to lack of knowledge. Our company reserves the right to change the information provided.

This product is manufactured by Betek A.Ş. with certificate of conformity to the standards TS ISO / IEC TS EN ISO 9001, TS EN ISO 14001, TS 18001, TS EN ISO 50001, TS ISO 10002, TS ISO/IEC 27001.